

Connector - PLD E 608-CO-FS - 2702309

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Socket for power supply and series connection, black, 3-pos.



Key Commercial Data

Packing unit	5 pc
Minimum order quantity	5 pc
GTIN	 4 055626 113357
GTIN	4055626113357

Technical data

General

Type	Installation coupler
Color	black
Connection method	Screw connection
Number of positions	3
Note number of positions	2+PE
Tightening torque contact carrier	0.3 Nm
Number of connections	3
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	14

Cabel

External cable diameter	7.5 mm ... 8.5 mm (3x 1.5 mm ²)
	9.5 mm ... 10.5 mm (3x 2.5 mm ²)
Stripping length for sheath	7 mm

Connector - PLD E 608-CO-FS - 2702309

Technical data

Ambient conditions

Degree of protection	IP20
	IP40 (plugged in)
Ambient temperature (operation)	70 °C
Ambient temperature (storage/transport)	-30 °C ... 70 °C

Electrical characteristics

Rated current	16 A (according to EN 61984 at 70 °C)
Rated voltage (I/2)	250 V
Rated surge voltage (I/2)	2.5 kV

Mechanical characteristics

QUICKON connectability	5 (according to EN 61984)
Insertion/withdrawal cycles	10 (according to EN 61984)

Material data

Contact material	Brass
Contact surface material	surface-protected
Flammability rating according to UL 94	V2
Degree of pollution	2

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27440312
eCl@ss 11.0	27440312
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440312
eCl@ss 9.0	27440312

ETIM

ETIM 6.0	EC002641
ETIM 7.0	EC002641

Connector - PLD E 608-CO-FS - 2702309

Classifications

UNSPSC

UNSPSC 13.2	39121419
UNSPSC 18.0	39121419
UNSPSC 19.0	39121419
UNSPSC 20.0	39121419
UNSPSC 21.0	39121419

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 118976
---------------	---	---	---------------

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 118976
----------------	---	---	---------------

cULus Recognized			
------------------	---	--	--

Phoenix Contact 2021 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>