

Cable - CABLE-D-37SUB/F/OE/0,25/S/2,0M - 2926250

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Assembled shielded round cable; connection 1: Single wires (37-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 37-position); cable length: 2 m

Your advantages

- ✓ Individual wire marking: 1, 2, 3, 4, etc.
- ✓ Individual wires fitted with ferrules
- ✓ Connector according to IEC 60807-2/DIN 41652
- ✓ Screw connection: 2 UNC 4-40 screws
- ✓ D-SUB socket or pin strip at one end
- ✓ Open end at one end
- ✓ Shield connection: H05V-K 1 mm² cable, black, 0.5 m in length
- ✓ 1:1 connection



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 548045
GTIN	4046356548045

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation)
	-10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Maximum altitude	≤ 2000 m
Degree of protection	IP20
	≥ IP54 (Installation location)

General

Max. permissible operating voltage	25 V AC
------------------------------------	---------

Cable - CABLE-D-37SUB/F/OE/0,25/S/2,0M - 2926250

Technical data

General

	60 V DC
Max. current carrying capacity per path	2 A (see to derating)
Nominal operating mode	100% operating factor

Cable

Length of cable	2 m
Type of cable	Assembled shielded round cable
Single wires, quantity	14
Single wire, material	Cu uninsulated
Single wire, cross section	0.25 mm ²
Single wire, cross section [AWG]	24
Wire diameter incl. insulation	1.2 mm ±0.05 mm
External cable diameter	10.8 mm ±0.5 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Halogen-free cable	No
Smallest bending radius, fixed installation	90 mm
Smallest bending radius, movable installation	170 mm
Bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Cable insulation resistance	≥ 20 MΩ/km (at 20 °C)
Cable resistance	≤ 80 Ω/km (at 20 °C)
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Gasoline resistance	can withstand occasional splashes (raw cable)

Connection data

Connection name	Field level
Connection method	D-SUB socket strip
Number of connections	1
Number of positions	37
Torque	0.2 Nm
Insertion/withdrawal cycles	> 200

Connection data 2

Connection name	Controller level
Connection method	Single wires

Cable - CABLE-D-37SUB/F/OE/0,25/S/2,0M - 2926250

Technical data

Connection data 2

Number of positions	37
Note	The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.

Standards and Regulations

Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Gasoline resistance	can withstand occasional splashes (raw cable)
Connection in acc. with standard	CUL
Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178
Rated insulation voltage	125 V
Rated surge voltage	1.2 kV
Insulation	Functional insulation
Pollution degree	2
Overvoltage category	II

Supported controller

Controller	universal
------------	-----------

Color code

Connector 1 = connector 2 (optional) = wire color	D-SUB37 (1) = white
	D-SUB37 (2) = brown
	D-SUB37 (3) = green
	D-SUB37 (4) = yellow
	D-SUB37 (5) = gray
	D-SUB37 (6) = pink
	D-SUB37 (7) = blue
	D-SUB37 (8) = red
	D-SUB37 (9) = black
	D-SUB37 (10) = violet
	D-SUB37 (11) = gray-pink
	D-SUB37 (12) = red-blue
	D-SUB37 (13) = white-green
	D-SUB37 (14) = brown-green
	D-SUB37 (15) = white-yellow
	D-SUB37 (16) = yellow-brown
	D-SUB37 (17) = white-gray
	D-SUB37 (18) = gray-brown

Cable - CABLE-D-37SUB/F/OE/0,25/S/2,0M - 2926250

Technical data

Color code


	D-SUB37 (19) = white-pink
	D-SUB37 (20) = pink-brown
	D-SUB37 (21) = white-blue
	D-SUB37 (22) = brown-blue
	D-SUB37 (23) = white-red
	D-SUB37 (24) = brown-red
	D-SUB37 (25) = white-black
	D-SUB37 (26) = brown-black
	D-SUB37 (27) = gray-green
	D-SUB37 (28) = yellow-gray
	D-SUB37 (29) = pink-green
	D-SUB37 (30) = yellow-pink
	D-SUB37 (31) = green-blue
	D-SUB37 (32) = yellow-blue
	D-SUB37 (33) = green-red
	D-SUB37 (34) = yellow-red
	D-SUB37 (35) = green-black
	D-SUB37 (36) = yellow-black
	D-SUB37 (37) = gray-blue

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Diagram



Maximum permissible current per path in uncoiled state

Classifications

eCl@ss

eCl@ss 10.0.1	27242220
---------------	----------

Cable - CABLE-D-37SUB/F/OE/0,25/S/2,0M - 2926250

Classifications

eCl@ss

eCl@ss 11.0	27242220
eCl@ss 4.0	27060300
eCl@ss 4.1	27060300
eCl@ss 5.0	27242200
eCl@ss 5.1	27242200
eCl@ss 6.0	27249200
eCl@ss 7.0	27249205
eCl@ss 9.0	27242220

ETIM

ETIM 2.0	EC000237
ETIM 3.0	EC000237
ETIM 4.0	EC000237
ETIM 6.0	EC000237
ETIM 7.0	EC000237

UNSPSC

UNSPSC 6.01	26121620
UNSPSC 7.0901	26121620
UNSPSC 11	26121620
UNSPSC 12.01	26121620
UNSPSC 13.2	26121620
UNSPSC 18.0	26121620
UNSPSC 19.0	26121620
UNSPSC 20.0	26121620
UNSPSC 21.0	26121620

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

Cable - CABLE-D-37SUB/F/OE/0,25/S/2,0M - 2926250

Approvals

CSA		http://www.csagroup.org/services-industries/product-listing/	70002966
Nominal voltage UN		125 V	
Nominal current IN		1 A	

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal voltage UN		125 V	
Nominal current IN		2 A	

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal voltage UN		125 V	
Nominal current IN		2 A	

EAC		RU* DE.HB*35.B00385
-----	--	------------------------

cULus Recognized	
------------------	--

Accessories

Accessories

Marker carrier cable

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable binders, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

Phoenix Contact 2021 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>