0800235

https://www.phoenixcontact.com/in/products/0800235



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Fabric label, Roll, yellow, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 20 mm x 8 mm, Number of individual labels: 2500

Your advantages

- · The EMLC label consists of a textile foil with very low restoring forces
- · Enables labels to be stuck over edges and curves
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- · Labeling service: Phoenix Contact can custom-label all EMLC ... markers in accordance with your requirements

Commercial Data

Item number	0800235
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BG2
Product Key	BG2411
Catalog Page	Page 333 (C-3-2019)
GTIN	4046356570787
Weight per Piece (including packing)	175 g
Weight per Piece (excluding packing)	165.4 g
Customs tariff number	39269097
Country of origin	DE

0800235

https://www.phoenixcontact.com/in/products/0800235



Technical Data

Product properties

Product type	Device marking
Marking	
Number of individual labels	2500
Number of individual labels per row	4
Ambient conditions	
Ambient temperature (operation)	-40 °C 150 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Mounting	
Mounting type	adhesive
Material specifications	
RoHS compliant	yes
Foil strength	50 µm
Adhesive strength	20 µm
Adhesive	Acrylic
Color	yellow
Material	PA

Environmental and real-life conditions

Components

Test for substances that would hinder coating with paint or varnish

	VW PV 3.10.7:2005-02
Result	Test passed
UV resistance	
Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

free from silicone and halogen

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05	
Result	Test passed	
Climate level	AHT 1.0 S	
Cycles	2	
Salt spray test		
Specification	ISO 9227:2012-05	
Result	Test passed	

0800235

https://www.phoenixcontact.com/in/products/0800235



Ambient conditions

Ambient temperature (operation)	-40 °C 150 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Recommended humidity (storage/transport) mensions	50 %
	50 %

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)



0800235

https://www.phoenixcontact.com/in/products/0800235



Classifications

ECLASS

ECLASS-10.0.1 27400629 ECLASS-11.0 27281103	ECLASS-9.0	27400629
ECLASS-11.0 27281103	ECLASS-10.0.1	27400629
	ECLASS-11.0	27281103

ETIM

	ETIM 8.0	EC001288
UN	UNSPSC	
	UNSPSC 21.0	39131500

0800235

https://www.phoenixcontact.com/in/products/0800235



Accessories

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110 - 5145384 https://www.phoenixcontact.com/in/products/5145384



Ink ribbon, for roll printers for printing the product groups TML..., WML..., WML HF..., WML-FLAG..., EML..., EML-ESD..., EML-RM..., EML-HA..., EMLS..., EMLC..., EMLP... and PMM..., width: 110 mm, color: black

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110/50 - 0800687 https://www.phoenixcontact.com/in/products/0800687



Ink ribbon, for roll printers for printing the product groups TML..., WML..., WML HF..., WML-FLAG..., EML.., EML-ESD..., EML-RM..., EML-HA..., EMLS..., EMLC..., EMLP... and PMM..., width: 110 mm, color: black

0800235

https://www.phoenixcontact.com/in/products/0800235



Cable marker carrier

Cable marker carrier - KME - 0807083 https://www.phoenixcontact.com/in/products/0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

Phoenix Contact 2022 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in