

Insert label - EMT (31X12,5)R



0800008

<https://www.phoenixcontact.com/in/products/0800008>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Insert label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: insert, lettering field size: 31 x 12.5 mm, Number of individual labels: 500

Your advantages

- Thanks to their special shape, the EMT (31x12,5)R insert labels remain securely inside the collar of the Siemens controller once inserted
- Quick and inexpensive marking with THERMOMARK ... roll printers from Phoenix Contact
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- Marking service: Phoenix Contact can custom-mark all EMT ... markers according to your requirements

Commercial Data

Item number	0800008
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BG2
Product Key	BG2411
Catalog Page	Page 343 (C-3-2019)
GTIN	4046356914482
Weight per Piece (including packing)	133.2 g
Weight per Piece (excluding packing)	133.2 g
Customs tariff number	39269097
Country of origin	DE

Insert label - EMT (31X12,5)R



0800008

<https://www.phoenixcontact.com/in/products/0800008>

Technical Data

Product properties

Product type	Device marking
--------------	----------------

Marking

Number of individual labels	500
Number of individual labels per row	2

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C / 50 % relative humidity

Mounting

Mounting type	insert
---------------	--------

Material specifications

Foil strength	175 µm
Color	white
Material	Polyester
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

	VDMA 24364-A1-L:2018-05
Result	Test passed

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
---------------	---------------------------------------

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 200 °C (230 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03
---------------	--------------------------------------

Insert label - EMT (31X12,5)R



0800008

<https://www.phoenixcontact.com/in/products/0800008>

	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
	Test passed
	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C / 50 % relative humidity
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Dimensions

Width	31 mm
Length	12.5 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Insert label - EMT (31X12,5)R



0800008

<https://www.phoenixcontact.com/in/products/0800008>

Classifications

ECLASS

ECLASS-9.0	27400629
ECLASS-10.0.1	27400629
ECLASS-11.0	27281106

ETIM

ETIM 8.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131700
-------------	----------

Insert label - EMT (31X12,5)R

0800008

<https://www.phoenixcontact.com/in/products/0800008>



Accessories

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110-WMTB HF - 5148007

<https://www.phoenixcontact.com/in/products/5148007>



Ink ribbon, for roll printer for printing product groups WMTB HF..., WMS-2 HF..., TMT..., EMT..., EMLF..., PML-..., width: 110 mm, color: black

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in