

# Insert label - EMT (50X26)R



0800052

<https://www.phoenixcontact.com/in/products/0800052>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Insert label, For marking Siemens ET 200S controllers, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: insert, lettering field size: 50 x 26 mm, Number of individual labels: 500

## Your advantages

- EMT (50x26)R, white insert label, for marking Siemens ET 200S controllers
- Thanks to their special shape, the EMT (50x26)R insert labels remain securely inside the collar of the Siemens controller once inserted
- Quick and inexpensive marking with THERMOMARK ... roll printers from Phoenix Contact
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- Marking service: Phoenix Contact can custom-mark all EMT ... markers according to your requirements

## Commercial Data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 0800052                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to Order (non-returnable) |
| Sales Key                            | BG2                            |
| Product Key                          | BG2411                         |
| Catalog Page                         | Page 343 (C-3-2019)            |
| GTIN                                 | 4046356545464                  |
| Weight per Piece (including packing) | 360.6 g                        |
| Weight per Piece (excluding packing) | 360.6 g                        |
| Customs tariff number                | 39269097                       |
| Country of origin                    | DE                             |

# Insert label - EMT (50X26)R



0800052

<https://www.phoenixcontact.com/in/products/0800052>

## Technical Data

### Product properties

|                 |   |
|-----------------|---|
| Product type    | Device marking                          |
| Controller type | For marking Siemens ET 200S controllers |

### Marking

|                                     |     |
|-------------------------------------|-----|
| Number of individual labels         | 500 |
| Number of individual labels per row | 2   |

### Marking technology

|              |                         |
|--------------|-------------------------|
| Device       | 5146477 THERMOMARK ROLL |
|              | 5145274 THERMOMARK X1.1 |
|              | 5146231 THERMOMARK X1.2 |
| Printability | Thermal transfer        |

### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 120 °C   |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

### Mounting

|               |        |
|---------------|--------|
| Mounting type | insert |
|---------------|--------|

### Material specifications

|               |                                |
|---------------|--------------------------------|
| Foil strength | 175 µm                         |
| Color         | white                          |
| Material      | Polyester                      |
| Components    | free from silicone and halogen |

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

|        |                         |
|--------|-------------------------|
|        | VDMA 24364-A1-L:2018-05 |
| Result | Test passed             |

#### Scratch test for the determining scratch resistance

|               |                                       |
|---------------|---------------------------------------|
| Specification | DIN EN ISO 1518-1:2019-10 (following) |
|---------------|---------------------------------------|

#### Tesafilm test

|               |                                  |
|---------------|----------------------------------|
| Specification | DIN EN ISO 2409:2013 (following) |
| Result        | Test passed                      |

#### UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result        | Test passed                    |
| Test duration | 96 h                           |

# Insert label - EMT (50X26)R



0800052

<https://www.phoenixcontact.com/in/products/0800052>

## Temperature resistance

|                        |                                 |
|------------------------|---------------------------------|
| Specification          | ANSI/UL 969-2018:03 (following) |
| Test duration          | 240 h                           |
| Rating 200 °C (230 °C) | Test passed                     |

## Wipe resistance of inscriptions

|               |  |
|---------------|--|
| Specification | DIN EN 61010-1 (VDE 0411-01):2020-03           |
|               | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
|               | Test passed                                    |
|               | Test passed                                    |
| Specification | ISO 175:2010 (following)                       |
| Test duration | 168 h  |
|               | Test passed                                    |

## Testing in a condensation changing climate in the presence of sulfur dioxide

|               |                   |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result        | Test passed       |
| Climate level | AHT 1.0 S         |
| Cycles        | 2                 |

## Salt spray test

|               |                           |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result        | Test passed               |
| Test duration | 96 h                      |

## Ambient conditions

|   |   |
|---|---|
| Ambient temperature (operation)                     | -40 °C ... 120 °C   |
| Recommended storage conditions                      | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |
| Recommended ambient temperature (storage/transport) | 23 °C   |
| Recommended humidity (storage/transport)            | 50 %  |

## Dimensions

|        |       |
|--------|-------|
| Width  | 50 mm |
| Length | 26 mm |

## Standards and regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

# Insert label - EMT (50X26)R

0800052

<https://www.phoenixcontact.com/in/products/0800052>



## Classifications

### ECLASS

|               |          |
|---------------|----------|
| ECLASS-9.0    | 27400629 |
| ECLASS-11.0   | 27281106 |
| ECLASS-10.0.1 | 27400629 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC001530 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131700 |
|-------------|----------|

# Insert label - EMT (50X26)R

0800052

<https://www.phoenixcontact.com/in/products/0800052>



## Accessories

### Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110-WMTB HF - 5148007

<https://www.phoenixcontact.com/in/products/5148007>



Ink ribbon, for roll printer for printing product groups WMTB HF..., WMS-2 HF..., TMT..., EMT..., EMLF..., PML-..., width: 110 mm, color: black

---

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)