

0800345

https://www.phoenixcontact.com/in/products/0800345

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Safety label with special adhesive, Roll, silver, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 40 x 15 mm, Number of individual labels: 1000

Your advantages

- The EMLS is a tamper-proof label that can be used as a rating plate or a sealing label
- When detaching, a part of the metallized layer separates. It leaves a triangular pattern on the label and substrate. The safety function is reliable
 up to 80°C
- · When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- · Labeling service: Phoenix Contact can custom-label all EMLS ... markers according to your requirements
- The EMLS ... materials are UL-listed

Commercial Data

Item number	0800345
item number	0600345
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	BG2
Product Key	BG2411
Catalog Page	Page 339 (C-3-2019)
GTIN	4046356580144
Weight per Piece (including packing)	216.3 g
Weight per Piece (excluding packing)	216.3 g
Customs tariff number	39199080
Country of origin	DE



0800345

https://www.phoenixcontact.com/in/products/0800345

Technical Data

Product properties

Product type	Device marking
larking	
Number of individual labels	1000
Number of individual labels per row	2
Marking technology	
Device	1085260 THERMOMARK ROLL 2.0
	0804501 THERMOMARK ROLLMASTER 300
	0804663 THERMOMARK ROLLMASTER 600
Ink ribbon	5145384 THERMOMARK-RIBBON 110
Printability	Thermal transfer
File number	UL-MH48542 / PC-014

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

RoHS compliant	yes
Foil strength	53 μm
Adhesive strength	20 μm
Adhesive	Acrylic
Color	silver
Material	Polyester
Components	free from silicone and halogen

Environmental and real-life conditions

	Specification	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Testing in a condensation changing climate in the presence of sulfur dioxide	Testing in a condensation changing climate in the presence of sulfur d	ioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Ambient conditions

Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Dimensions



0800345

https://www.phoenixcontact.com/in/products/0800345

	Length	15 mm
Standards and regulations		
	Wipe resistance	DIN EN 61010-1 (VDE 0411-1)



0800345

https://www.phoenixcontact.com/in/products/0800345

Approvals



UL RecognizedApproval ID: FILE MH 48542



0800345

https://www.phoenixcontact.com/in/products/0800345

Classifications

UNSPSC 21.0

ECLASS

ECLASS-9.0	27400629
ECLASS-10.0.1	27400629
ECLASS-11.0	27281103
ETIM	
ETIM 8.0	EC001288
UNSPSC	

39131500



0800345

https://www.phoenixcontact.com/in/products/0800345

Accessories

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110 - 5145384 https://www.phoenixcontact.com/in/products/5145384



Ink ribbon, for roll printers for printing the product groups TML..., WML..., WML HF..., WML-FLAG..., EML..., EML-ESD..., EML-RM..., EML-HA..., EMLS..., EMLC..., EMLP... and PMM..., width: 110 mm, color: black

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110/50 - 0800687 https://www.phoenixcontact.com/in/products/0800687



Ink ribbon, for roll printers for printing the product groups TML..., WML..., WML HF..., WML-FLAG..., EML..., EML-ESD..., EML-RM..., EML-HA..., EMLS..., EMLC..., EMLP... and PMM..., width: 110 mm, color: black




0800345

https://www.phoenixcontact.com/in/products/0800345

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110 BU - 0829544 https://www.phoenixcontact.com/in/products/0829544





Phoenix Contact 2022 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in