

CABLE-D15SUB/S/S/300/KONFEK/S - Cable



2305622

<https://www.phoenixcontact.com/in/products/2305622>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Assembled shielded round cable; connection 1: D-SUB pin strip (1x 15-position); connection 2: D-SUB pin strip (1x 15-position); cable length: 3 m

Commercial Data

Item number	2305622
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	CK2
Product Key	CK2135
Catalog Page	Page 571 (C-5-2019)
GTIN	4046356011969
Weight per Piece (including packing)	356.1 g
Weight per Piece (excluding packing)	343.3 g
Customs tariff number	85444290
Country of origin	DE

Technical Data

Product properties

Product type	System cable
Insulation characteristics	
Insulation	Functional insulation
Insulation characteristics: Air clearances and creepage distances	
Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

Electrical properties

Max. permissible operating voltage	25 V AC
	60 V DC
Nominal operating mode	100% operating factor
Max. current carrying capacity per path	2 A (see to derating)

Air clearances and creepage distances

Rated insulation voltage	125 V
Rated surge voltage	1.2 kV

Cable/line

Cable length	3 m
15X0.25 [PVC]	
Number of positions	15
Shielded	yes
Cable type	15X0.25 [PVC]
Conductor type	Assembled shielded round cable
Conductor structure signal line	14x 0.15 mm
AWG signal line	24
Conductor cross section	15x 0.25 mm ²
Wire diameter incl. insulation	1.2 mm ±0.05 mm
External cable diameter	7.9 mm ±0.5 mm

CABLE-D15SUB/S/S/300/KONFEK/S - Cable



2305622

<https://www.phoenixcontact.com/in/products/2305622>

Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Bare Cu litz wires
Cable resistance	≤ 80 Ω/km (at 20 °C)
Insulation resistance	≥ 20 MΩ*km (at 20 °C)
Smallest bending radius, fixed installation	67 mm
Smallest bending radius, movable installation	126 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)

color code

D-SUB15 (1)	D-SUB15 (1) = white
D-SUB15 (2)	D-SUB15 (2) = brown
D-SUB15 (3)	D-SUB15 (3) = green
D-SUB15 (4)	D-SUB15 (4) = yellow
D-SUB15 (5)	D-SUB15 (5) = gray
D-SUB15 (6)	D-SUB15 (6) = pink
D-SUB15 (7)	D-SUB15 (7) = blue
D-SUB15 (8)	D-SUB15 (8) = red
D-SUB15 (9)	D-SUB15 (9) = black
D-SUB15 (10)	D-SUB15 (10) = violet
D-SUB15 (11)	D-SUB15 (11) = gray-pink
D-SUB15 (12)	D-SUB15 (12) = red-blue
D-SUB15 (13)	D-SUB15 (13) = white-green
D-SUB15 (14)	D-SUB15 (14) = brown-green
D-SUB15 (15)	D-SUB15 (15) = white-yellow

Connection data

Field level

Connection method	D-SUB pin strip
Number of connections	1
Number of positions	15
Tightening torque	0.2 Nm
Insertion/withdrawal cycles	> 200

Controller level

Connection method	D-SUB pin strip
Number of connections	1

CABLE-D15SUB/S/S/300/KONFEK/S - Cable



2305622

<https://www.phoenixcontact.com/in/products/2305622>

Number of positions	15
Tightening torque	0.2 Nm
Insertion/withdrawal cycles	> 200


Standards and regulations

Air clearances and creepage distances

Standards/regulations	DIN EN 50178
-----------------------	--------------

Drawings

Diagram



Maximum permissible current per path in uncoiled state

CABLE-D15SUB/S/S/300/KONFEK/S - Cable



2305622

<https://www.phoenixcontact.com/in/products/2305622>

Approvals



CSA

Approval ID: 70002966



cUL Recognized

Approval ID: FILE E 238705



UL Recognized

Approval ID: FILE E 238705



EAC

Approval ID: RU*-DE.HB*35.B00385

CABLE-D15SUB/S/S/300/KONFEK/S - Cable



2305622

<https://www.phoenixcontact.com/in/products/2305622>

Classifications

ECLASS

ECLASS-10.0.1	27242220
ECLASS-11.0	27242220
ECLASS-12.0	27242220
ECLASS-13.0	27242220

ETIM

ETIM 8.0	EC000237
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

CABLE-D15SUB/S/S/300/KONFEK/S - Cable



2305622

<https://www.phoenixcontact.com/in/products/2305622>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

CABLE-D15SUB/S/S/300/KONFEK/S - Cable



2305622

<https://www.phoenixcontact.com/in/products/2305622>

Accessories

KME - Cable marker carrier

0807083

<https://www.phoenixcontact.com/in/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 x 8 mm

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in