

D-ST 2,5-QUATTRO-0,8 OG - End cover



3030513

<https://www.phoenixcontact.com/in/products/3030513>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

End cover, length: 72 mm, width: 0.8 mm, height: 29 mm, color: orange



Commercial Data

| | |
|--------------------------------------|--------------------|
| Item number | 3030513 |
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales Key | BE2 |
| Product Key | BE2Z1X |
| Catalog Page | Page 71 (C-1-2019) |
| GTIN | 4046356714037 |
| Weight per Piece (including packing) | 1.594 g |
| Weight per Piece (excluding packing) | 1.528 g |
| Customs tariff number | 85389099 |
| Country of origin | DE |

D-ST 2,5-QUATTRO-0,8 OG - End cover



3030513

<https://www.phoenixcontact.com/in/products/3030513>

Technical Data

Product properties

| | |
|--------------|-----------|
| Product type | End cover |
|--------------|-----------|

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Ambient temperature (operation) | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Material specifications

| | |
|---|--------|
| Color | orange |
| Material | PA |
| Flammability rating according to UL 94 | V0 |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |

Dimensions

| | |
|--------|--------|
| Width | 0.8 mm |
| Height | 29 mm |
| Length | 72 mm |

Notes

| | |
|--------------------|--|
| Notes on operation | Bridges or reducing bridges cannot be used over the cover. |
|--------------------|--|

D-ST 2,5-QUATTRO-0,8 OG - End cover



3030513

<https://www.phoenixcontact.com/in/products/3030513>

Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-10.0.1 | 27141133 |
| ECLASS-11.0 | 27141133 |
| ECLASS-12.0 | 27141133 |
| ECLASS-13.0 | 27250301 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000886 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

D-ST 2,5-QUATTRO-0,8 OG - End cover



3030513

<https://www.phoenixcontact.com/in/products/3030513>

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in