

PV-C-M/F-PRO/F-1500/20-EU-SPR - Fuse plug



1623411

<https://www.phoenixcontact.com/in/products/1623411>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Fuse connector for protecting modules and devices in photovoltaic systems, black, SUNCLIX pin connector pattern, 1500 V/20 A, IP68 (24 h/2 m)

Product Description

SUNCLIX fuse connector for 1500 V system voltage, fuse-link nominal current of 20 A, EU version, version with spacer for better heat dissipation when bundling

Commercial Data

Item number	1623411
Packing unit	8 pc
Minimum order quantity	8 pc
Product Key	ABLBEA
GTIN	4055626141497
Weight per Piece (including packing)	22.22 g
Weight per Piece (excluding packing)	22.22 g
Country of origin	DE

Technical Data

Product properties

Product type	Photovoltaic connector
Product family	Sunclix


Insulation characteristics

Degree of pollution	2
---------------------	---

Electrical properties

Rated voltage (II/2)	1000 V
Rated voltage (III/2)	1500 V
Rated surge voltage (II/2)	12 kV
Rated surge voltage (III/2)	16 kV
Rated surge voltage (III/3)	12 kV
Fuse-link nominal current	20 A DC (Nominal current of the fuse-link)
Fuse adapter nominal current	17 A DC

Dimensions

Dimensional drawing	
Width	24 mm
Height	26.4 mm
Length	220.8 mm

Material specifications

Color of the housing part	black
Flammability rating according to UL 94	V0
Insulating material group	I / CTI 600
Contact material	Cu
Contact surface material	Ag
Contact carrier material	PPE
O-ring material	Silopren LSR 2660
Housing material	PPE

Environmental and real-life conditions

Ambient conditions

Degree of protection (when plugged in)	IP66 / IP68 (2 m / 24 h)
Degree of protection	IP66 / IP68 (2 m / 24 h)
Ambient temperature (operation)	-40 °C ... 50 °C

PV-C-M/F-PRO/F-1500/20-EU-SPR - Fuse plug




1623411

<https://www.phoenixcontact.com/in/products/1623411>

Drawings

Dimensional drawing



PV-C-M/F-PRO/F-1500/20-EU-SPR - Fuse plug



1623411

<https://www.phoenixcontact.com/in/products/1623411>

Classifications

ETIM

ETIM 7.0	EC002635
----------	----------

PV-C-M/F-PRO/F-1500/20-EU-SPR - Fuse plug



1623411

<https://www.phoenixcontact.com/in/products/1623411>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in