



CCVA 2,5/...-G-5,08P26THRR... 5.08 mm Pitch



Note:

COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of pos.	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
Taped header with side panels , plug-in direction vertical to the PCB, 5.08 mm pitch, color: black					
	2	5.08	CCVA 2,5/2-G-5,08P26THRR32	19 55 96 3	140
	3	10.16	CCVA 2,5/3-G-5,08P26THRR32	19 55 97 6	
	4	15.24	CCVA 2,5/4-G-5,08P26THRR32	19 55 98 9	
	5	20.32	CCVA 2,5/5-G-5,08P26THRR56	19 55 99 2	
	6	25.40	CCVA 2,5/6-G-5,08P26THRR56	19 56 00 1	
	7	30.48	CCVA 2,5/7-G-5,08P26THRR56	19 56 01 4	
	8	35.56	CCVA 2,5/8-G-5,08P26THRR56	19 56 02 7	
	9	40.64	CCVA 2,5/9-G-5,08P26THRR88	19 56 03 0	
	10	45.72	CCVA 2,5/10-G-5,08P26THRR88	19 56 04 3	
	11	50.80	CCVA 2,5/11-G-5,08P26THRR88	19 56 05 6	
	12	55.88	CCVA 2,5/12-G-5,08P26THRR88	19 56 06 9	
(1) Coding element , inserted into the recess on the header after the reflow assembly process, red insulation material			 CR-MSTB	17 34 40 1	
(2) HT coding element ¹⁾ , inserted into the recess on the header before the reflow process, made of high temperature resistant beige plastic			 CR-MSTB NAT HT	19 54 36 2	100
(3) Marker card , with 12 pcs. 10-section marker strips, white, self-adhesive, for 120 terminal blocks			SK 5,08/3,8 (see COMBICON catalog)		
Technical data			see description		
Dimensions				5.08	
Pitch		[mm]		1.5	
Hole diameter		[mm]		1x1	
Pin dimensions		[mm]x[mm]			
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		-		IIIa	
Surge voltage category / contamination class		-/-	III / 3	III / 2	II / 2
Rated voltage		[V]	250	320	400
Rated surge voltage		[kV]	4	4	4
Nominal current / cross section		[A]/[mm ²]		12 / -	
Maximum load current / cross section		[A]/[mm ²]		12 / -	
Insulating material				LCP	
Inflammability class in acc. with UL 94				V0	

Dimensional drawings, see page 7.

Dimensional drawings of tapes, see page 20.

¹⁾ Pre-coded taped articles are available on request.