

MSTBO 2,5/ 3-G1L

Order No.: 1861028

Illustration shows different articles for putting together the upper part of the housing

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1861028>Header, Pitch: 5 mm, Number of positions: 3, Color: green, Assembly:
Soldering

Commercial data	
EAN	4017918133382
Pack	50 pcs.
Customs tariff	85369010
Weight/Piece	0.001847 KG
Catalog page information	Page 256 (CC-2009)

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CB, CSA, CUL, GOST, UL, VDE-PZI

CSA

Nominal voltage U_N	300 V
Nominal current I_N	10 A

CUL

Nominal voltage U_N	300 V
Nominal current I_N	10 A

UL

Nominal voltage U_N	300 V
Nominal current I_N	10 A

Accessories


Item	Designation	Description
Assembly		
1759981	MSTB-BF	Mounting flange, for fixing both ends of the header onto the PCB, green insulating material, with M 2 x 14 screws and nuts.
1755477	MSTB-BL	Keying cap, for forming sections, plugs onto header pin, green insulating material

General

2199618	CR MSTBO-G1	
---------	-------------	--

Drawings

Schematic diagram



Pin assignment left

MSTBO 2,5/ 3-G1L Order No.: 1861028

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1861028>

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2009 Phoenix Contact
Technical modifications reserved;