

SACC-DSI-M12MS-8CON-PG9/0,5 VA

Order No.: 1554694



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1554694>

Sensor/actuator flush-type connector, 8-pos., M12, rear/screw mounting with PG9 thread, with 0.5 m TPE litz wire, 8 x 0.25 mm², high-grade steel version

Commercial data

| | |
|--------------------------|--------------------|
| EAN | 4046356170390 |
| Pack | 1 pcs. |
| Customs tariff | 85366990 |
| Weight/Piece | 0.0296 KG |
| Catalog page information | Page 144 (PC-2009) |

Product notes

WEEE/RoHS-compliant since:
11/10/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

| | |
|--------------------------------|--------|
| Nominal current I _N | 2 A |
| Nominal voltage U _N | 30 V |
| Number of positions | 8 |
| Volume resistance | ≤ 3 mΩ |

| | |
|---------------------------------|--|
| Insulation resistance | ≥ 100 MΩ |
| Length of cable | 0.5 m |
| Ambient temperature (operation) | -25 °C ... 85 °C (plug/socket) |
| | -25 °C ... 90 °C (cable, fixed installation) |

General characteristics

| | |
|------------------------------------|---|
| Coding | A - standard |
| Inflammability class acc. to UL 94 | V0 |
| Surge voltage category | II |
| Pollution degree | 3 |
| Degree of protection | IP67/IP69K |
| Contact material | CuZn |
| Contact surface material | Au |
| Contact carrier material | PA 66 |
| Material, knurls | High-grade steel |
| Sealing material | NBR |
| Mounting type | Rear mounting, Pg9 thread with lock nut |
| Type of connection | Individual wires |
| Status display | No |

Conductor data

| | |
|------------------------------------|--|
| Cable type | TPE litz wire |
| Conductor cross section | 0.25 mm ² |
| AWG signal line | 24 |
| Conductor structure, signal line | 14x 0.15 mm |
| Core diameter including insulation | 1.15 mm ±0.07 mm |
| Thickness, insulation | 0.21 mm |
| Wire colors | Brown, blue, white, gray, pink, green, yellow, red |
| Insulation resistance | ≥ 20 MΩ*km |
| Conductor resistance | ≤ 80 Ω/km |
| Nominal voltage, conductor | 300 V |
| Test voltage, conductor | 2000 V AC |
| Material conductor insulation | TPE |
| Conductor material | Tin-plated Cu litz wires |

Address

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact
Technical modifications reserved;