

**VS-08-ST-H21-RJ45**

Order No.: 1652729

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1652729>

RJ45 male insert, CAT6, 8-pos., shielded, IDC displacement connection, for litz wire AWG 25 ... 24 and solid wires AWG 24, with strain relief

**Ethernet****Commercial data**

EAN	4017918952853
Pack	5 pcs.
Customs tariff	85366990
Weight/Piece	0.00439 KG
Catalog page information	Page 192 (PC-2009)

**Product notes**

WEEE/RoHS-compliant since:  
11/13/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****Mechanical characteristics**

Number of positions	8
Number of slots	1
Insertion/withdrawal cycles	≥ 750
Type of connection	IDC cutting

Conductor cross section	0.2 mm <sup>2</sup> ... 0.5 mm <sup>2</sup> (Solid and stranded)
Connection cross section AWG	24 ... 27 (Solid and stranded)
Cable exit	Straight
Ambient temperature (operation)	-25 °C ... 60 °C

#### Material data

Contact carrier material	PC
Contact material	Phosphor bronze
Contact surface material	Gold
Inflammability class acc. to UL 94	V2

#### Electrical characteristics

Number of positions	8
Transmission characteristics (category)	CAT6
Rated current	1 A
Pollution degree	2

#### Accessories

Item	Designation	Description
<b>Bend protection sleeve</b>		
1654756	VS-08-KS-H/GN	RJ45 bend protection sleeve, for pin inserts VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, for cable cross section up to 7 mm, color: green
1654743	VS-08-KS-H/GY	RJ45 bend protection sleeve, for pin inserts VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, for cable cross section up to 7 mm, color: gray

#### Sleeve housing


1652732	VS-08-T-H-RJ45/IP67	RJ45 sleeve housing, IP67, for pin insert VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, with push-pull interlocking for panel mounting frames, for cable cross section 5.0 mm ... 8.5 mm, color: gray
1658671	VS-08-T-H-RJ45/IP67-BK	RJ45 sleeve housing, IP67, for pin insert VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, with push-pull interlocking for panel mounting frames, for cable cross section 5.0 mm ... 8.5 mm, color: black
1652855	VS-08-T-H-S-RJ45/IP67	RJ45 sleeve housing, IP67, irradiated for welding applications, for pin inserts VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, with push-pull interlocking for panel mounting frames, cable cross section 5.0 mm ... 8.5 mm

**Tools**

1653265	VS-CT-RJ45-H	Crimp tool, pliers with die, for RJ45 pin inserts VS-08-ST-H...-RJ45
---------	--------------	--

**Drawings**

Dimensioned drawing



**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact  
Technical modifications reserved;