


VS-04-BUA-FK-F/IP67

Order No.: 1653854

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1653854>

USB socket insert, 4-pos., socket USB type A on flat-ribbon cable terminal strip, pitch 2.54, for the Freenet system in the panel mounting frame, IP20 terminal outlet, 19" patch panel and service interface

Commercial data	
EAN	4017918970185
Pack	1 pcs.
Customs tariff	85366990
Weight/Piece	0.0144 KG
Catalog page information	Page 310 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
02/29/2008

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Mechanical characteristics	
Number of positions	4
Insertion/withdrawal cycles	≥ 1000
Type of connection	Flat-ribbon cable connection, pitch 2.54 mm
Ambient temperature (operation)	-15 °C ... 65 °C

Material data

Housing material	PC
Contact carrier material	PET
Contact material	Copper alloy
Contact surface material	Gold over nickel
Degree of protection	IP20
Inflammability class acc. to UL 94	V0


Electrical characteristics

Rated voltage (III/3)	30 V
Rated current	1 A
Insulation resistance	≥ 1 GΩ

Drawings

Schematic diagram

Pin	USB A
1	VBUS
2	
3	Shield
4	
5	D-
6	D+
7	Shield
8	
9	GND
10	



Contact assignment

Address

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact
Technical modifications reserved;