

VS-09-ST-DSUB-HD-EG

Order No.: 1655111

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655111>

D-SUB contact insert, shell size 1, with 15 signal contacts, contact type pin, with solder cup, straight, fixing with a 3 mm hole, for panel mounting frame VS-09-...

Commercial data	
EAN	4046356029056
Pack	10 pcs.
Customs tariff	85369010
Weight/Piece	0.00626 KG
Catalog page information	Page 319 (PC-2009)

Product notesWEEE/RoHS-compliant since:
06/09/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Mechanical characteristics**

Number of positions	15
Insertion/withdrawal cycles	≥ 200
Type of connection	Solder cup
Conductor cross section	0.34 mm ²

Connection cross section AWG	22
Insertion force per signal contact	≤ 3.40 N
Ambient temperature (operation)	-55 °C ... 125 °C

Material data

Housing material	Steel, yellow chromated
Contact carrier material	Polyester GF
Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel
Inflammability class acc. to UL 94	V0


Electrical characteristics

Rated voltage (III/3)	60 V
Rated surge voltage	1 kV
Rated current	3 A

Drawings

Dimensioned drawing

D-SUB contact insert



Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact
Technical modifications reserved;