

VS-09-DSUB-20-LI-1,0

Order No.: 1656233

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1656233>

Assembled D-SUB cable shielded, 9-pos., stranded (7-wire), cable color RAL 7000 (gray), IP20 degree of protection, head 1 with socket shell 1 and straight cable outlet, head 2 with pin shell 1 and straight cable outlet, length: 1 m

Commercial data

| | |
|--------------------------|--------------------|
| EAN | 4046356029711 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Weight/Piece | 0.10 KG |
| Catalog page information | Page 326 (PC-2009) |

Product notesWEEE/RoHS-compliant since:
09/19/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Mechanical characteristics**

| | |
|-----------------------------|------|
| Number of positions | 9 |
| Insertion/withdrawal cycles | ≥ 50 |
| External cable diameter | 6 mm |

| | |
|---------------------------------|----------------|
| Cable exit | Straight |
| Length of cable | 1 m |
| Ambient temperature (operation) | 0 °C ... 70 °C |

Material data

| | |
|--------------------------|--------------|
| Housing material | PVC |
| Contact material | Copper alloy |
| Contact surface material | Gold-plated |
| Outer sheath, material | PVC |
| Degree of protection | IP20 |

Electrical characteristics

| | |
|-----------------------|-------|
| Rated voltage (III/3) | 125 V |
| Rated current | 1 A |

Address

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact
Technical modifications reserved;