

FLK 50-PA/EZ-DR/KS/1000/YUC

Order No.: 2314325

Illustration shows the product FLK 50-PA/EZ-DR/KS/ 200/YUC

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2314325>

Round cable set, with two 50-pos. molded socket strips (1:1 connection). Length of cable: 10.0 m

Commercial data

EAN	4046356101974
Pack	1 pcs.
Customs tariff	85444290
Weight/Piece	2.0649 KG
Catalog page information	Page 222 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
01/01/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Nominal voltage U_N	30 V DC
Max. current carrying capacity per path	500 mA (Up to 55°C ambient temperature)
Max. conductor resistance	0.16 Ω /m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Number of positions	50
Number of positions, control side	50
Number of connectors, control side	1
Number of positions, module side	50
Number of connectors, modul side	1
Fixed cable length	10 m
Single wire, cross section	0.14 mm ²
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	11 mm

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact
Technical modifications reserved;