

# CABLE-FCN40/1X50/ 4,0M/M340

Order No.: 2321677



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2321677>

Assembled round cable (40-pos. Fujitsu strip on 50-pos. FLK strip) for coupling 32 channels to I/O cards of MODICON® M340 (BMX DDI 3202K, BMX DDI 6402K, BMX DD0 3202K, BMX DD0 6402K, BMX DDM 3202K); cable length 4 m

| Commercial data          |                    |
|--------------------------|--------------------|
| EAN                      | 4046356412506      |
| Pack                     | 1 pcs.             |
| Customs tariff           | 85444290           |
| Weight/Piece             | 0.60 KG            |
| Catalog page information | Page 205 (IF-2009) |

## Product notes

WEEE/RoHS-compliant since:  
07/17/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

| General                                 |           |
|---|-----------|
| Nominal voltage $U_N$                   | < 50 V AC |
|   | 60 V DC   |
| Max. current carrying capacity per path | 1 A       |

|   |                      |
|---|----------------------|
| Max. conductor resistance                     | 0.16 $\Omega$ /m     |
| Ambient temperature (operation)               | -20 °C ... 50 °C     |
| Ambient temperature (storage/transport)       | -20 °C ... 70 °C     |
| Number of positions                           | 50                   |
| Number of positions, control side             | 40                   |
| Number of connectors, control side            | 1                    |
| Number of positions, module side              | 50                   |
| Number of connectors, modul side              | 1                    |
| Fixed cable length                            | 4 m                  |
| Single wire, cross section                    | 0.14 mm <sup>2</sup> |
| AWG   | 26                   |
| Conductor construction: Number of litz wires: | 7                    |
| Single wire, material                         | Cu tin-plated        |
| External diameter                             | 10.5 mm              |
| Shielding                                     | no                   |

**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact  
Technical modifications reserved;