

# CABLE-FCN40/1X50/ 1,0M/M340

Order No.: 2321648



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2321648>

Assembled round cable (40-pos. Fujitsu strip on 50-pos. FLK strip) for coupling 32 channels to I/O cards of MODICON® M340 (BMX DDI 3202K, BMX DDI 6402K, BMX DD0 3202K, BMX DD0 6402K, BMX DDM 3202K); cable length 1 m

Commercial data	
EAN	4046356412490
Pack	1 pcs.
Customs tariff	85444290
Weight/Piece	0.1714 KG
Catalog page information	Page 205 (IF-2009)

## Product notes

WEEE/RoHS-compliant since:  
07/17/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

General	
Nominal voltage $U_N$	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A

Max. conductor resistance	0.16 $\Omega$ /m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions	50
Number of positions, control side	40
Number of connectors, control side	1
Number of positions, module side	50
Number of connectors, modul side	1
Fixed cable length	1 m
Single wire, cross section	0.14 mm <sup>2</sup>
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	10.5 mm
Shielding	no

**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact  
Technical modifications reserved;