

GMSTBVA 2,5/ 2-G-7,62 BK

Order No.: 1728954

<http://eshop.phoenixcontact.com.cn/phoenix/treeViewClick.do?UID=1728954>

Header, Nominal current: 12 A, Number of positions: 2, Pitch: 7.62 mm, Color: Black, Contact surface: Tin

Commercial data

Pack	50 pcs.
Customs tariff	85366990
Gross weight in pieces	1.25 g

Product notes

WEEE/RoHS-compliant since:
2003-01-01



Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions / positions

Pitch	7.62 mm
Dimension a	7.62 mm
Number of positions	2

Technical data

Range of articles	GMSTBVA 2,5/...-G
Connection in acc. with standard	EN-VDE
Nominal current I_N	12 A
Nominal voltage U_N	400 V
Color	Black
Nominal voltage, UL/CUL Use Group B	250 V

Nominal current, UL/CUL Use Group B	12 A
Nominal voltage, UL/CUL Use Group D	300 V
Nominal current, UL/CUL Use Group D	10 A

Certificates



Certification

CSA, cULus Recognized, GOST, VDE Gutachten mit
Fertigungsüberwachung, IECEE CB Scheme

Certifications applied for:

Certification Ex:

Address

Phoenix Contact China
No. 36 Phoenix Road - Jiangning Development Zone
211100 Nanjing, China
Phone 86-25-52121888
Fax 86-25-52121555
<http://www.phoenixcontact.com.cn>

PHOENIX CONTACT Middle East FZ LLC
Technical modifications reserved;