

High Current Connectors - HV M8/2 - 3049550

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




High Current Connectors, Connection method: Bolt connection, Cross section: 2.5 mm² - 50 mm², AWG: 14 - 1/0, Width: 21 mm, Height: 63.5 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

Why buy this product

- ✓ Comprehensive range of accessories for safe and user-friendly wiring of conductors up to 120 mm²
- ✓ Two different partition plates can be used for the range of single and double-bolt terminal blocks
- ✓ 2 and 3-pos. connection rails can be used for potential distribution
- ✓ Spring washers are used to prevent hexagonal nuts from loosening
- ✓ Secure connection of up to 4 conductors with cable lugs according to DIN 46234, 46235, and 46237 in a small amount of space
- ✓ The feed-through window provided in the partition plates can be easily removed for mounting the connection rails



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 25 pc |
| Minimum order quantity | 25 pc |
| GTIN |  4 046356 310307 |
| Weight per Piece (excluding packing) | 99.99 g |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

General

| | |
|---|------|
| Number of levels | 1 |
| Number of connections | 2 |
| Color | gray |
| Insulating material | PA |
| Inflammability class according to UL 94 | V0 |
| Rated surge voltage | 8 kV |
| Pollution degree | 3 |
| Surge voltage category | III |
| Insulating material group | I |

High Current Connectors - HV M8/2 - 3049550

Technical data

General

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal current I_N | 150 A |
| Nominal voltage U_N | 1000 V |
| Open side panel | nein |
| Surge voltage test setpoint | 9.8 kV |
| Result of surge voltage test | Test passed |
| Power frequency withstand voltage setpoint | 2.2 kV |
| Result of power-frequency withstand voltage test | Test passed |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed |
| Tight fit on carrier | NS 35 |
| Setpoint | 10 N |
| Result of tight fit test | Test passed |
| Requirements, voltage drop | ≤ 3.2 mV |
| Result of voltage drop test | Test passed |
| Temperature-rise test | Test passed |
| Conductor cross section short circuit testing | 50 mm ² |
| Short-time current | 6 kA |
| Short circuit stability result | Test passed |
| Proof of thermal characteristics (needle flame) effective duration | 10 s |
| Result of thermal test | Test passed |
| Test specification, oscillation, broadband noise | DIN EN 50155 (VDE 0115-200):2008-03 |
| Test spectrum | Service life test category 1, class B, body mounted |
| Test frequency | $f_1 = 5$ Hz to $f_2 = 150$ Hz |
| ASD level | 0.02 g ² /Hz |
| Acceleration | 0.8 g |
| Test duration per axis | 5 h |
| Test directions | X-, Y- and Z-axis |
| Oscillation, broadband noise test result | Test passed |
| Test specification, shock test | DIN EN 50155 (VDE 0115-200):2008-03 |
| Shock form | Half-sine |
| Acceleration | 5 g |
| Shock duration | 30 ms |
| Number of shocks per direction | 3 |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |
| Shock test result | Test passed |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 120 °C |

Dimensions

| | |
|--------|-------|
| Length | 67 mm |
| Width | 21 mm |

High Current Connectors - HV M8/2 - 3049550

Technical data

Dimensions

| | |
|------------------|---------|
| Height | 63.5 mm |
| Height NS 35/7,5 | 66 mm |
| Height NS 35/15 | 73.5 mm |

Connection data

| | |
|--|---------------------|
| Conductor cross section solid min. | 2.5 mm ² |
| Conductor cross section solid max. | 50 mm ² |
| Conductor cross section stranded min. | 2.5 mm ² |
| Conductor cross section stranded max. | 50 mm ² |
| Conductor cross section AWG/kcmil min. | 14 |
| Conductor cross section AWG/kcmil max | 1/0 |
| Screw thread | M8 |
| Tightening torque, min | 6 Nm |
| Tightening torque max | 12 Nm |
| Connection method | Bolt connection |
| Connection in acc. with standard | DIN 46 234 |
| Min. cross section | 2.5 mm ² |
| Max. cross section | 50 mm ² |
| Bolt diameter | 8 mm |
| Tightening torque, min | 6 Nm |
| Tightening torque max | 12 Nm |
| Connection in acc. with standard | DIN 46,235 |
| Min. cross section | 6 mm ² |
| Max. cross section | 35 mm ² |
| Bolt diameter | 8 mm |
| Tightening torque, min | 6 Nm |
| Tightening torque max | 12 Nm |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000897 |
|----------|----------|

High Current Connectors - HV M8/2 - 3049550

Classifications

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Approvals

Approvals


Approvals


GOST / CSA / CSAus / GOST / cCSAus

Ex Approvals

Approvals submitted

Approval details

| |
|--|
| GOST  |
|--|

| | |
|---|--------|
| CSA  | |
| mm ² /AWG/kcmil | 3 |
| Nominal current I _N | 130 A |
| Nominal voltage U _N | 1000 V |

| | |
|----------------------------|---|
| CSAus | |
| mm ² /AWG/kcmil | 3 |

High Current Connectors - HV M8/2 - 3049550

Approvals

| | |
|--------------------------------|--------|
| Nominal current I _N | 130 A |
| Nominal voltage U _N | 1000 V |

GOST 

cCSAus

Accessories

Accessories

Bridge

Connection element - HV M8/1-VS 2 - 3049369



Connection element, Number of positions: 2, Color: silver

Connection element - HV M8/1-VS 3 - 3049372



Connection element, Number of positions: 3, Color: silver

Mounting rail

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

High Current Connectors - HV M8/2 - 3049550

Accessories

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119



DIN rail 35 mm (NS 35)

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122



DIN rail 35 mm (NS 35)

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704



DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421



DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

High Current Connectors - HV M8/2 - 3049550

Accessories

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

End cap - NS 35/ 7,5 CAP - 1206560



DIN rail end piece, for DIN rail NS 35/7.5

Drawings

Circuit diagram

