

## ZB 9:UNBEDRUCKT

Order No.: 0829127

The illustration shows the variants of the ZB 5



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=0829127>

Zack marker strip, Strip, white, unlabeled, can be labeled with: Plotter,  
Mounting type: Snap into tall marker groove, for terminal block width: 9  
mm, Lettering field: 9 x 10.5 mm

### Commercial data

|                          |                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| EAN                      | <br>4 046356 546423 |
| sales group              | B101                                                                                                  |
| Pack                     | 10 Pcs.                                                                                               |
| Customs tariff           | 39269097                                                                                              |
| Gross weight in pieces   | 0.002219 KG                                                                                           |
| Net weight per piece     | 0.002219 KG                                                                                           |
| Catalog page information | Page 72 (C-5-2013)                                                                                    |

### Product notes

WEEE/RoHS-compliant since:  
11/12/2009



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Dimensions

|            |         |
|------------|---------|
| Length (b) | 10.5 mm |
| Width (a)  | 9 mm    |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 100 °C |
|---------------------------------|-------------------|

#### General

|                                         |                                |
|-----------------------------------------|--------------------------------|
| Note                                    | Can be labeled with CMS        |
|                                         | Can be labeled with CMS        |
| Color                                   | white                          |
| Components                              | free from silicone and halogen |
| Inflammability class according to UL 94 | V2                             |
| Material                                | PA                             |
|                                         | PA                             |
| Wipe resistance                         | DIN EN 61010-1 (VDE 0411-1)    |
|                                         | DIN EN 61010-1 (VDE 0411-1)    |
|                                         | DIN VDE 0611                   |
|                                         | DIN VDE 0611                   |
| Number of individual labels             | 10                             |
| Number of individual labels per row     | 10                             |
| Number of marker strips                 | 10                             |
| Marking mounting type                   | Snap into tall marker groove   |

#### Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

---

#### Accessories

| Item           | Designation | Description                                                      |
|----------------|-------------|------------------------------------------------------------------|
| <b>General</b> |             |                                                                  |
| 5144699        | CMS-P1-M/ZB | Plastic magazine for CMS-P1 plotter. Accepts 22 Zack band strips |

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;