

## AI 16 -12 WH


Order No.: 3200140

The figure shows the version AI 0,5-6 WH

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=3200140>

Ferrule, Sleeve length: 12 mm, Length: 20 mm, Color: white

### Commercial data

EAN	 4 017918 093792
sales group	B250
Pack	100 Pcs.
Customs tariff	85369010
Gross weight in pieces	0.00076 KG
Net weight per piece	0.00075 KG

### Product notes

WEEE/RoHS-compliant since:  
01/01/2005

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Dimensions

Length (b)	20 mm
Maximum stripping length	16 mm
Sleeve length	12 mm
Inner dimension of the insulating collar (d)	6.2 mm
Ferrule diameter	3.5 mm

Insulating collar thickness	0.4 mm
Sleeve wall thickness	0.2 mm

**Ambient conditions**

Short-term temperature	120 °C
Max. permanent temperature	105 °C

**General**

Color	white
Components	free from silicone and halogen
Inflammability class according to UL 94	HB
Material	E-CU

**Certificates / Approvals**



Certification

CSA

Certifications applied for:

Certification Ex:

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;