

## AI 16 -18 BU


Order No.: 3200629

The figure shows the version AI 0.75-8 BU

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=3200629>

Ferrule, Sleeve length: 18 mm, Length: 29 mm, Color: blue

### Commercial data

EAN	 4 017918 094232
sales group	B250
Pack	100 Pcs.
Customs tariff	85369010
Gross weight in pieces	0.000973 KG
Net weight per piece	0.000973 KG
Catalog page information	Page 445 (C-5-2013)

### Product notes

WEEE/RoHS-compliant since:  
01/01/2005

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Dimensions

Length (b)	29 mm
Maximum stripping length	22 mm
Sleeve length	18 mm
Inner dimension of the insulating collar (d)	8.8 mm
Ferrule diameter	5.8 mm
Insulating collar thickness	0.4 mm
Sleeve wall thickness	0.2 mm

**Ambient conditions**

Short-term temperature	120 °C
Max. permanent temperature	105 °C

**General**

Color	blue
Components	free from silicone and halogen
Inflammability class according to UL 94	HB
Material	E-CU

**Certificates / Approvals**




Certification cCSAus

Certifications applied for:

Certification Ex:

**Drawings**

Dimensioned drawing



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;