

VIP-CAB-FLK20/FR/OE/0,14/0,5M


Order No.: 2900138

The figure shows the 14-pos. version



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2900138>

Assembled round cable with a 20-pos. molded socket strip (90° output) and an open end. On the open end, the wires are labeled with 1 to 20 and have ferrules, cable length: 0.5 m

Commercial data	
EAN	 4 046356 476935
Note	Made-to-order
sales group	I580
Pack	1 Pcs.
Customs tariff	85444290
Gross weight in pieces	0.0624 KG
Net weight per piece	0.0624 KG
Catalog page information	Page 503 (C-7-2013)

Product notes

WEEE/RoHS-compliant since:
04/01/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
General	
Nominal voltage U_N	< 50 V AC 60 V DC
Max. current carrying capacity per path	1 A
Max. conductor resistance	0.16 Ω /m
Length of cable	0.5 m
Single wire, cross section	0.14 mm ²

AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	7.6 mm
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding	no

Environmental conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Flame resistance	IEC 60332-1

Connector, module side

Number of positions	20
Connectors	IDC/FLK socket strip (2.54 mm)
Number of plugs	1

Connector, controller side

Number of positions	20
Connectors	Open end
Number of plugs	0

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;