


RAD-PIG-EF316-N-SMA

Order No.: 2867694



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2867694>

Adapter cable, 30 cm pigtail, N (female) -> SMA (male), 50 Ω impedance

Commercial data	
EAN	 4 017918 939069
sales group	H178
Pack	1 Pcs.
Customs tariff	85442000
Gross weight in pieces	0.0545 KG
Net weight per piece	0.0459 KG
Catalog page information	Page 465 (C-8-2013)

Product notes

WEEE/RoHS-compliant since: 10/01/2005



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Dimensions	
Fixed cable length	30 cm
External diameter	2.50 mm
Ambient conditions	
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

General

Connection 1	Connector connection
Connection method	SMA (male)
Connection 2	Connector connection
Connection method	N (female)
Cable type	EF 316
Outer sheath, material	RADOX®(LSFH)
Minimum bending radius	12.50 mm
Frequency range	900 MHz
	2.4 GHz
	5 GHz
Impedance	50 Ω

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;