


VS-M16 (3-6)

Order No.: 1688450

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1688450>D-SUB cap nut with line seal, for sleeve housing VS-09-..., conductor
diameter of 3 mm ... 6 mm**Commercial data**

EAN	 4 017918 818371
sales group	D500
Pack	5 Pcs.
Customs tariff	39269097
Gross weight in pieces	0.00319 KG
Net weight per piece	0.00319 KG
Catalog page information	Page 219 (C-2-2013)

Product notesWEEE/RoHS-compliant since:
04/05/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Mechanical characteristics**

External cable diameter	3 mm ... 6 mm
Color	gray

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	-20 °C ... 80 °C
Degree of protection	IP67

Material data

Inflammability class according to UL 94	V0
Housing material	PA
Sealing material	Neoprene
Seal material	Neoprene

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;