

VS-25-A-GC-BU/BU

Order No.: 1689734



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1689734>

D-SUB panel mounting frame, shell size 3, with 25 signal contacts,
socket, gender changer, shielded, IP67 degree of protection

Commercial data

EAN	 4 017918 934118
Note	Made-to-order
sales group	D504
Pack	5 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.02981 KG
Net weight per piece	0.02924 KG
Catalog page information	Page 221 (C-2-2013)

Product notes

WEEE/RoHS-compliant since:
03/01/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Mechanical characteristics

Number of positions	25
Insertion/withdrawal cycles	≥ 200
Color	gray

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Degree of protection	IP67

Material data

Inflammability class according to UL 94	V0
Housing material	PA

Contact carrier material	Polyester GF
Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel
Material	Plastic
Sealing material	Flat gasket: NBR; profile gasket: EPDM
Seal material	Flat gasket: NBR; profile gasket: EPDM

Electrical characteristics

Rated voltage (III/3)	125 V
Rated current	5 A

Certificates / Approvals

Certification

Certifications applied for:


Certification Ex:

Accessories

Item	Designation	Description
Protective covers		
1652211	VS-25-SD	D-SUB protective cover, shell size 3, IP54 degree of protection, for panel mounting frame and sleeve housing VS-25-...

Drawings

Dimensioned drawing



D-SUB panel mounting frame

Panel cutout: VS-25-A...

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;