


MSTBO 2,5/ 3-G1R BK

Order No.: 2909633

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2909633>

Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Assembly: Soldering

Commercial data

EAN	 4 017918 405182
sales group	F057
Pack	200 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.001738 KG
Net weight per piece	0.001738 KG

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Dimensions**

Pitch	5 mm
Dimension a	10 mm
Hole diameter	1.4 mm

General

Range of articles	MSTBO 2,5/...-G1R
Insulating material group	IIIa
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV
Rated voltage (III/3)	250 V
Rated voltage (III/2)	320 V
Rated voltage (II/2)	400 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	12 A
Maximum load current	12 A
Insulating material	PBT
Inflammability class according to UL 94	V0
Number of positions	3

Certificates / Approvals



Certification

CSA, cULus Recognized, VDE Gutachten mit
 Fertigungsüberwachung, CCA, IEC/IEC CB Scheme

Certifications applied for:

Certification Ex:

Accessories

Item	Designation	Description
General		
2199618	CR MSTBO-G1	Coding section

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;