

MSTBO 2,5/ 3-G1L BK


Order No.: 2909646



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2909646>

Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Assembly: Soldering

Commercial data

EAN	 4 017918 236663
sales group	F057
Pack	200 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.001764 KG
Net weight per piece	0.0016 KG

Product notes

WEEE/RoHS-compliant since:
01/01/2003



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions

Pitch	5 mm
Dimension a	10 mm
Hole diameter	1.4 mm

General

Range of articles	MSTBO 2,5/...-G1L
Insulating material group	IIIa
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV
Rated voltage (III/3)	250 V
Rated voltage (III/2)	320 V
Rated voltage (II/2)	400 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	12 A
Maximum load current	12 A
Insulating material	PBT
Inflammability class according to UL 94	V0
Number of positions	3

Certificates / Approvals



Certification

CSA, cULus Recognized, VDE Gutachten mit
 Fertigungsüberwachung, CCA, IECEE CB Scheme

Certifications applied for:

Certification Ex:

Accessories

Item	Designation	Description
General		
2199618	CR MSTBO-G1	Coding section

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;