

FFKDSA1/V1-5,08-10 BD:1-10Q

Order No.: 1741173

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1741173>

PCB terminal block, Nominal current: 15 A, Nom. voltage: 320 V,
Pitch: 5.08 mm, Number of positions: 10, Connection method: Spring-
cage connection, Mounting: Soldering, Conductor/PCB connection
direction: 90 °, Color: green

Commercial data

EAN	 4 046356 291934
Note	Made-to-order
sales group	E060
Pack	50 Pcs.
Customs tariff	85369010
Gross weight in pieces	0.011282 KG
Net weight per piece	0.010514 KG

Product notesWEEE/RoHS-compliant since:
05/03/2007

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Dimensions**

Length	12.7 mm
Pitch	5.08 mm
Dimension a	45.72 mm
Pin dimensions	0,5 x 1 mm
Hole diameter	1.3 mm

General

Range of articles	FFKDS(A)/V1
-------------------	-------------

Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV
Rated voltage (III/3)	320 V
Rated voltage (III/2)	320 V
Rated voltage (II/2)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	15 A
Nominal cross section	1.5 mm ²
Solder pin surface	Sn
Stripping length	10 mm
Number of positions	10

Connection data

Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	16

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;