

IBS RBC METER/F-T


Order No.: 2723123

The illustration shows the versions standard, highly flexible and remote bus cables for underground runs



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2723123>

Remote bus cable for flexible installation, sold by the meter

Commercial data	
EAN	 4 017918 132552
Note	Made-to-order
sales group	K900
Pack	1 m
Customs tariff	85444993
Gross weight in pieces	0.07068 KG
Net weight per piece	0.07068 KG
Catalog page information	Page 333 (C-8-2013)

Product notes

WEEE/RoHS-compliant since:
04/01/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Ambient conditions

Ambient temperature (operation)	-30 °C ... 70 °C (flexible)
	-40 °C ... 80 °C (fixed routing)
Ambient temperature (storage/transport)	-40 °C ... 80 °C

External sheath

Outer sheath, material	PUR mixture halogen-free
External sheath, color	Green RAL 6017

External diameter	8.1 mm
Single wire	
Single wire, color	Green-yellow, white-brown, gray-pink
Single wire, cross section	0.22 mm ²
Structural data	32-strand Litz wires, fine-stranded
Mechanical properties	
Smallest bending radius, movable installation	15 x 8,1 mm

Certificates / Approvals



Certification GOST, INTERBUS CLUB

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;