

## PSM-SET-FSMA/4-HCS


Order No.: 2799487



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2799487>

F-SMA plug set for HCS fiber, for self assembly consisting of 4 quick mounting connectors with bend protection sleeve

### Commercial data

EAN	 4 017918 126742
sales group	H628
Pack	1 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.0381 KG
Net weight per piece	0.03706 KG
Catalog page information	Page 402 (C-8-2013)

### Product notes

WEEE/RoHS-compliant since:  
05/09/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General

Type of plug	F-SMA/Type 905, IEC 874-2
FO fiber	HCS fiber
Attenuation	< 2 dB

## Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

---

## Accessories

Item	Designation	Description
<b>Cable/conductor</b>		
1402191	FOC-HCS-RUGGED-1014/...	rugged HCS installation cable for inner areas with highly tear-proof aramid strain-relief elements. Individual elements made from highly flexible FRNC material. The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2901555	FOC-HCS-RUGGED-1014/IP20/...	rugged HCS installation cable (IP20 heads only) for inner areas with highly tear-proof aramid strain-relief elements. Individual elements made from highly flexible FRNC material. The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2901557	FOC-HCSO-1015/IP20/...	Highly rugged HCS round cable (IP20 heads only) for assembly and for outdoor installation with integrated moisture barrier as well as rodent-proof scrim. Individual elements made from highly flexible FRNC material. The wire is ozone and UV resistant with a very rugged polyethylene outer sheath.
2799885	PSM-LWL-HCS-RUGGED-200/230	HCS cable, duplex 200/230 µm, by the meter, without connector, for indoor installation
2799445	PSM-LWL-HCSO-200/230	HCS cable, duplex 200/230 µm, by the meter, without connector, for outdoor installation
<b>Tools</b>		
2799526	PSM-HCS-KONFTOOL	HCS assembly kit for F-SMA quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS fibers, and documentation

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;