

PSM-SET-FSMA/4-KT


Order No.: 2799720



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2799720>

F-SMA plug set for polymer fiber, for self assembly consisting of 4 quick mounting connectors with bend protection sleeve

Commercial data

EAN	 4 017918 156053
sales group	H628
Pack	1 Pcs.
Customs tariff	85367000
Gross weight in pieces	0.034 KG
Net weight per piece	0.0323 KG
Catalog page information	Page 402 (C-8-2013)

Product notes

WEEE/RoHS-compliant since:
08/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Type of plug	F-SMA/Type 905, IEC 874-2
FO fiber	Polymer fiber
Attenuation	< 1.5 dB

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Accessories

Item	Designation	Description
Cable/conductor		
2313397	FL FOC PN-B-980/1000	PROFINET polymer fiber cable, duplex, 980/1000 µm, heavy-weight design, for permanent indoor installation, by the meter, without connector
2313407	FL FOC PN-C-FLEX-980/1000	PROFINET polymer fiber cable, duplex, 980/1000 µm, heavy-weight highly flexible design, for flexible cable conduit applications, by the meter, without connector
2901553	FOC-KDHEAVY-1011/IP20/...	POF installation cable (IP20 heads only) for fixed installation in the inner area with individual elements made of highly durable polyamide (PE). The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2901551	FOC-PN-B-1000/IP20/...	POF PROFINET installation cable (IP20 heads only) for fixed installation in the inner area with individual elements of highly durable polyamide (PE). Individual elements made of extremely wear-resistant polyamide (PE). The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2901552	FOC-PN-C-1003/IP20/□	Highly flexible POF PROFINET cable (IP20 heads only) for use in drag chains. Individual elements made from extremely wear-resistant polyamide (PE). The cable is halogen-free, ozone and UV resistant, and has a rugged polyurethane (PUR) outer sheath.
2901548	FOC-RUGGED-1012/IP20/...	Rugged POF installation cable (IP20 heads only) for fixed installation in the inner area. Individual elements made from extremely wear-resistant polyamide (PE). Halogen-free, ozone and UV resistant with a reinforced polyurethane (PUR) outer sheath.
2901549	FOC-RUGGED-FLEX-1013/IP20/...	Highly flexible POF round cable (IP20 heads only) for use in drag chains. Individual elements made from extremely wear-resistant polyamide (PE). The cable is halogen-free, ozone and UV resistant, and has a rugged polyurethane (PUR) outer sheath.
2744319	PSM-LWL-KDHEAVY-980/1000	Polymer fiber cable, duplex 980/1000 µm, medium-weight version for permanent indoor installation, by the meter, without connector
2744322	PSM-LWL-RUGGED-980/1000	Polymer fiber cable, duplex, 980 µm/1000 µm, heavy version for permanent indoor installation, sold by the meter without connectors

2744335	PSM-LWL-RUGGED-FLEX-980/1000	Polymer fiber cable, duplex 980/1000 µm, heavy-weight, highly flexible version for flexible conduit applications, by the meter, without connector
---------	------------------------------	---

Tools

2744131	PSM-POF-KONFTOOL	Polymer fiber DIY case, consisting of: Stripping knife, stripping pliers, polishing wheels for F-SMA and SCRJ quick mounting connectors, polishing pad and emery paper
---------	------------------	--

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;