


HC-M-KV-M20(11-16)

Order No.: 1645998

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1645998>

Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20

Commercial data

EAN	 4 017918 941260
sales group	D092
Pack	25 Pcs.
Customs tariff	74199990
Gross weight in pieces	0.04675 KG
Net weight per piece	0.04551 KG
Catalog page information	Page 553 (C-4-2013)

Product notes

WEEE/RoHS-compliant since:
02/16/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions

Wrench size, union nut	27 mm
Wrench size, support	27 mm
Length of the connecting thread	6 mm
External cable diameter	11 mm ... 16 mm

Ambient conditions

Degree of protection	IP68, to 5 bar
	IP68 (Up to 5 bar)
Ambient temperature (operation)	-20 °C ... 100 °C

General

Cable gland material	Nickel-plated brass
Seal material	Neoprene
Cable seal material	Neoprene
Material, O-ring	NBR
Shielded	No
Thread type on connection side	M20
Tightening torque, union nut	7.50 Nm

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;