


# HC-M-KV-M25(14-21)

Order No.: 1646007

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1646007>

Metal screw connection up to 5 bar, thread length: 7 mm, cable diameter: 14 - 21 mm, WAF 34, screw connection: M25

## Commercial data

EAN	 4 017918 941277
sales group	D092
Pack	25 Pcs.
Customs tariff	74199990
Gross weight in pieces	0.075 KG
Net weight per piece	0.075 KG
Catalog page information	Page 553 (C-4-2013)

## Product notes

WEEE/RoHS-compliant since:  
02/16/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Dimensions

Wrench size, union nut	34 mm
Wrench size, support	34 mm
Length of the connecting thread	7 mm
External cable diameter	14 mm ... 21 mm

**Ambient conditions**

Degree of protection	IP68, to 5 bar
	IP68 (Up to 5 bar)
Ambient temperature (operation)	-20 °C ... 100 °C

**General**

Cable gland material	Nickel-plated brass
Seal material	Neoprene
Cable seal material	Neoprene
Material, O-ring	NBR
Shielded	No
Thread type on connection side	M25
Tightening torque, union nut	10.00 Nm

**Certificates / Approvals**

Certification

Certifications applied for:

Certification Ex:

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;