


HC-M-KV-M32(19-27)

Order No.: 1646010

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1646010>

Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

Commercial data

EAN	 4 017918 941253
sales group	D092
Pack	10 Pcs.
Customs tariff	74199990
Gross weight in pieces	0.13117 KG
Net weight per piece	0.1205 KG
Catalog page information	Page 553 (C-4-2013)

Product notes

WEEE/RoHS-compliant since:
02/16/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions

Wrench size, union nut	34 mm
Wrench size, support	34 mm
Length of the connecting thread	8 mm
External cable diameter	19 mm ... 27 mm

Ambient conditions

Degree of protection	IP68, to 5 bar
	IP68 (Up to 5 bar)
Ambient temperature (operation)	-20 °C ... 100 °C

General

Cable gland material	Nickel-plated brass
Seal material	Neoprene
Cable seal material	Neoprene
Material, O-ring	NBR
Shielded	No
Thread type on connection side	M32
Tightening torque, union nut	15.00 Nm

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;