

VS-PPC-C1-RJ45-POBK-8I10G

Order No.: 1422205



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1422205>

RJ45 connector, IP67, with push/pull interlocking (Version 14), plastic housing, for 10 Gbps, for 24 ... 27 AWG stranded conductors

Commercial data

EAN	4 046356 571999
Note	Made-to-order
sales group	D512
Pack	1 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.0296 KG
Net weight per piece	0.0296 KG
Catalog page information	Page 80 (C-2-2013)

Product notes

WEEE/RoHS-compliant since:
03/26/2010



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Number of positions	8
Connection profile	RJ45 8(8)
Locking type	Push Pull
Shielded	Yes
Insertion/withdrawal cycles	≥ 750
Connection method	IDC

Conductor cross section	stranded
Connection cross section AWG	27 ... 24 (stranded)
External cable diameter	5 mm ... 8 mm
Cable exit	Straight
Color	black

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Degree of protection	IP65/67

Material data

Housing material	Plastic
------------------	---------

Electrical characteristics

Number of positions	8
Nominal voltage U_N	50 V
Nominal current I_N	1 A
Transmission characteristics (category)	CAT6 _A
Rated current	1 A
Pollution degree	2

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Accessories

Item	Designation	Description
Tools		
1657407	VS-CABLE-STRIP-VARIO	Stripping tool, for the multi-level stripping of shielded cables

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;