

IB IL 24 SEG/F-D-PAC

Order No.: 2861904

The illustration shows the product version IB IL 24 SEG/F-PAC



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2861904>

Inline segment terminal block, complete with accessories (connector and labeling field), 24 V DC, with fuse and diagnostics



Commercial data	
EAN	 4 017918 894603
sales group	K417
Pack	1 Pcs.
Customs tariff	85389091
Gross weight in pieces	0.0815 KG
Net weight per piece	0.06719 KG
Catalog page information	Page 199 (C-8-2013)

Product notes

WEEE/RoHS-compliant since:
06/28/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Dimensions	
Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm

Interfaces

Connection method	Inline data jumper
Interface	Inline local bus

Power supply

Typical current consumption	30 mA
I/O voltage	24 V DC
I/O voltage range	19.2 V DC ... 30 V DC
Max. current consumption	4 A
Fuse	SI 5 x 20 6, 300 AT (in scope of delivery)

General

Type of protection	Overload protection
Protective circuit/component	Fuse
Weight	42 g
Number of connectors	1

Inline potentials

Communications power U_L	7.5 V DC (via voltage jumper)
Current consumption from U_L	max. 25 mA
Current consumption from U_M	max. 4 A (nominal value)
Segment supply voltage U_S	24 V DC
Power supply at U_S	max. 4 A (nominal value)

Certificates / Approvals



Certification cULus Recognized, GOST

Certification Ex: cULus Listed

Certifications applied for:

Accessories

Item	Designation	Description
------	-------------	-------------

Connector/Adapter

2727637	IB IL SCN-PWR IN-CP	Connector, colored, for Inline power and segment terminal blocks
---------	---------------------	--

Marking

0809492	ESL 62X10	Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, Plotter: Laser printer, Mounting type: Insert, Lettering field: 62 x 10 mm
2727501	IB IL FIELD 2	Labeling field, width: 12.2 mm


Drawings

Connection diagram




**U_M and U_S connected internally
via fuse**

Block diagram



Dimensioned drawing



Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;