


**PTSA 1,5/ 2-3,5-Z BK**

Order No.: 1751765

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1751765>

PCB terminal block, Nominal current: 2 A, Nom. voltage: 250 V, Pitch:  
3.5 mm, Number of positions: 2, Connection method: Spring-cage  
connection, Mounting: Soldering, Conductor/PCB connection direction:  
45 °, Color: black

**Commercial data**

EAN	 4 046356 317870
Note	Made-to-order
sales group	E411
Pack	250 Pcs.
Customs tariff	85369010
Gross weight in pieces	0.00123 KG
Net weight per piece	0.0012 KG

**Product notes**WEEE/RoHS-compliant since:  
09/20/2007

[http://  
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)  
Please note that the data given  
here has been taken from the  
online catalog. For comprehensive  
information and data, please refer  
to the user documentation. The  
General Terms and Conditions of  
Use apply to Internet downloads.

**Technical data****Dimensions**

Length	12 mm
Height	13.1 mm
Pitch	3.5 mm
Dimension a	3.5 mm
Pin dimensions	0,4 x 0,75 mm
Pin spacing	3.5 mm
Hole diameter	1 mm

### General

Range of articles	PTSA 1,5
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	200 V
Rated voltage (III/2)	250 V
Rated voltage (II/2)	400 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	2 A
Nominal cross section	1.5 mm <sup>2</sup>
Stripping length	9 mm
Number of positions	2

### Connection data

Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	16

### Certificates / Approvals



Certification

cULus Recognized, GOST, VDE Gutachten mit  
Fertigungsüberwachung, CCA

Certifications applied for:

Certification Ex:

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;