


**PTSA 1,5/ 3-3,5-Z GY**

Order No.: 1995279

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1995279>

PCB terminal block, Nominal current: 2 A, Nom. voltage: 250 V, Pitch: 3.5 mm, Number of positions: 3, Connection method: Spring-cage connection, Mounting: Soldering, Conductor/PCB connection direction: 45 °, Color: Gray

**Commercial data**

EAN	 4 017918 991784
Note	Made-to-order
sales group	E411
Pack	250 Pcs.
Customs tariff	85369010
Gross weight in pieces	0.001747 KG
Net weight per piece	0.00152 KG

**Product notes**WEEE/RoHS-compliant since:  
11/10/2004

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****Dimensions**

Length	12 mm
Height	13.1 mm
Pitch	3.5 mm
Dimension a	7 mm
Pin dimensions	0,4 x 0,75 mm
Pin spacing	3.5 mm
Hole diameter	1 mm

### General

Range of articles	PTSA 1,5
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	200 V
Rated voltage (III/2)	250 V
Rated voltage (II/2)	400 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	2 A
Nominal cross section	1.5 mm <sup>2</sup>
Solder pin surface	Sn
Stripping length	9 mm
Number of positions	3

### Connection data

Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	16
Minimum AWG according to UL/CUL	24
Maximum AWG according to UL/CUL	16

### Certificates / Approvals



Certification

cULus Recognized, GOST, VDE Gutachten mit  
Fertigungsüberwachung, CCA

Certifications applied for:

Certification Ex:

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;