


NLC-MOD-USB

Order No.: 2701195



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2701195>

Serial connection to PC's USB port for data transfer or software configuration

Commercial data	
EAN	
sales group	K254
Pack	1 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.0411 KG
Net weight per piece	0.0398 KG
Catalog page information	Page 530 (C-8-2013)

Product notes

WEEE/RoHS-compliant since:
04/17/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

Slot 1 option module. Connects the Nanoline controller to a Type A USB port. Functions as a serial device and requires special driver included on nanoNavigator CD.

Technical data

Dimensions

Width	24.5 mm
Height	25.5 mm

Depth	49 mm
Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Interfaces	
Interface	USB
Connection method	USB Type B
Transmission length	2 m
Supply	
Supply voltage	24 V DC (Power available via logic module)
Max. current consumption	18 mA
Typical current consumption	10 mA

Certificates / Approvals



Certification UL Listed

Certifications applied for:

Certification Ex:

Accessories

Item	Designation	Description
General		
2701289	NLC-MOD-CAP	Replacement cover for slot 1 in base unit.
2701247	NLC-PC/USB-CBL 2M	Cable , serial

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;