

Search within category

Categories

Wire Termination

Terminals

Disconnects

BUY NOW

DESIGN / INSTALL

DNF14-250FIM-M

The vibration resistant male tab disconnect is made of brass and is nickel-plated. It is fully insulated in a blue, nylon housing. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 16-14 AWG (1.5-2.5 mm²). It is 0.90" (22.9 mm) long and 0.42" (10.7 mm) wide. The disconnect has a funnel entry configuration and a butted seam barrel. It comes in boxes of 1000.

Specs

Packaging Details

Tools

★ Add to Favorites

🛒 Add to BOM

Documents

Style	Male Tab Disconnect
Tab Size In. (mm)	0.250 x 0.032 (6.3 x 0.8)
UL Listed	Yes
Wire Range In. (mm²)	16 - 14 AWG (1.5 - 2.5)
Barrel Configuration	Funnel Entry
Barrel Type	Butted Seam
Base Material	Brass
Insulation	Nylon - Fully Insulated
Panduit Color Code	Blue
Plating Type	Nickel
Part Number Series	DNF-FIM
Length In (mm)	0.9 (22.9)
Max. Insulation Diameter In. (mm)	0.158 (4.08)
Width In (mm)	0.42 (10.7)
Wire Strip Length In. (mm)	9/32" (.2812) (7.1)
Flammability Rating	HB
Max. Voltage Rating	600V
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
CA-800/EZ Series Crimp Die	—
CA9 Series Crimp Die	—
Tool	CT-600-A, CT-1525, CT-2500
CSA Certified	C22.2 No.153
Standards	UL 310 Listed
Packaging Type	Box
Pieces Per Reel	—

http://www1.panduit.com/en/products-and-services/products/wire-termination/terminals/disconnects/DNF14-250FIM-M

1/2

9/7/2017		DNF14-250FIM-M Male Disconnect, nylon fully insulated, 16 - 14 AWG, .250 x .032 tab size Panduit	
Part Features		• Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost • Fully insulated design provides protection from electrical shorts • Internal barrel serrations assure good wire contact and maximum tensile strength • Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection • Coupler, male, and female parts sold separately • UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C) • UL and CSA rated up to 600 V per UL 310	
RoHS Compliancy Status		Compliant	
Min. Order Qty.		1,000	

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)