SOLUTIONS PRODUCTS AND SERVICES

SUPPORT ABOUT US

Q Search Panduit.com



Search within category

**BUY NOW** 

**DESIGN / INSTALL** 



## PRT3S-M

Pan-Ty® releasable tie, standard cross section, 11.5" (292mm) length, nylon 6.6, natural, bulk package.

Specs		Add to Favorites	Add to BOM
Std. Pkg. Qty.	1000		
Material	Nylon 6.6		
Application	General		
Color	Natural		
Cross Section	Standard		
Length (In.)	11.5		
Length (mm)	292		
Locking Style	Releasable		
Width (In.)	0.190		
Width (mm)	4.8		
Min. Loop Tensile Strength Lbs. (N)	50 (222)		
Plenum-Rated	Yes, AH-2		
UV Resistant	No		
Tool	Hand install only		
Length In (mm)	11.50 (292)		
Thickness In (mm)	0.05 (1.3)		
CE Compliant	Yes		
CSA Certified	Yes		
UL Listed (File #E56854)	Yes		
UL Recognized (File #E56854)	Yes		
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)		
Installation Temperature	-20°C - 0°C		
Operating Temperature	-60°C - 85°C		
Part Features	Release tab permits easy release and re-	use where changes are a	nticipated.
Releasable	Yes		
RoHS Compliancy Status	Compliant		
Min. Order Qty.	1,000.0000		