

Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT4H-C

Pan-Ty® locking tie, light-heavy cross section, 14.5" (368mm) length, nylon 6.6, natural, standard package.

Specs

Tools

Documents

★ Add to Favorites

Add to BOM

Std. Pkg. Qty.	100
Material	Nylon 6.6
Application	General
Color	Natural
Cross Section	Light-Heavy
Locking Style	Locking
Min. Loop Tensile Strength Lbs. (N)	120 (534)
Plenum-Rated	Yes, AH-2
Tool	GTH, GS4H, GS4EH, PTH, STH2, ST3EH
Length In (mm)	14.5 (368)
Thickness In (mm)	0.075 (1.9)
Bundle Diameter Range In. (mm)	0.19 (4.8) - 4.00 (102)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	MS3367-3-9
UL 62275 Compliant (Type 1, 11)	—
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Environment	Plenum
Installation Temperature	-20°C - 0°C
Operating Temperature	-60°C - 85°C
Part Features	One piece construction provides consistent, reliable performance. Low thread force.
Releasable	No
Thickness (mm)	1.9
Width In (mm)	0.30 (7.6)
RoHS Compliancy Status	Compliant

Min. Order Qty.

100.0000