

GO

BUY NOW

DESIGN / INSTALL



PLC1.5I-S8-M

Pan-Ty® locking clamp tie, intermediate cross section, #8 (M4) screw, 6.1" (155mm) length, nylon 6.6, natural, bulk package.

Specs	Packaging Details	Tools	Documents	★ Add to Favorites	🛒 Add to BOM
Material		Nylon 6.6			
Application		General			
Color		Natural			
Environment		Plenum			
Cross Section		Intermediate			
Length (In.)		6.1			
Length (mm)		155			
Locking Style		Locking			
Width (In.)		0.135			
Width (mm)		3.4			
Min. Loop Tensile Strength Lbs. (N)		40 (178)			
Plenum-Rated		Yes, AH-2			
Tool		GTS, GTSL, GS2B, PTS, PPTS, STS2			
Length In (mm)		6.10 (155)			
Nominal Hole Diameter In. (mm)		0.174 (4.4)			
Thickness In (mm)		0.045 (1.1)			
Width In (mm)		0.135 (3.4)			
Bundle Diameter Range In. (mm)		0.06 (1.5) - 1.25 (32)			
CE Compliant		Yes			
CSA Certified		Yes			
UL 62275 Compliant (Type 1, 11)		No			
UL 62275 Compliant (Type 2, 21)		Yes			
UL Listed (File #E56854)		Yes			
UL Recognized (File #E56854)		Yes			
Continuous Use Temperature Range		-76°F (-60°C) - 185°F (85°C)			
Installation Temperature		-4°F (-20°C) - 32°F (0°C)			



Operating Temperature

-76 °F (-60 °C) - 185 °F (85 °C)

Part Features

Used to secure a cable bundle to another surface such as a control panel,

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)

RoHS Compliancy Status

Compliant

Min. Order Qty.

1,000.0000