

Search within category

BUY NOW

DESIGN / INSTALL



PLT.6SM-M30

Pan-Ty®locking tie, subminiature cross section, 2.8" (71mm) length, heat stabilized nylon 6.6, black.

Specs

Packaging Details

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

Material	Heat Stabilized Nylon 6.6
Color	Black
Cross Section	Subminiature
Locking Style	Locking
Min. Loop Tensile Strength Lbs. (N)	8 (36)
Continuous Use Temperature Range	-76° (-60°) - 239° (115°)
Plenum-Rated	No
Tool	GTS, GTSL, PTS
Length In (mm)	2.8 (71)
Thickness In (mm)	0.030 (0.8)
Bundle Diameter Range In. (mm)	0.01 (0.3) - 0.60 (15)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	—
UL 62275 Compliant (Type 1, 11)	Yes
UL 62275 Compliant (Type 2, 21)	—
UL Listed (File #E56854)	No
UL Recognized (File #E56854)	Yes
Application	High Temperature
Environment	Indoor
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Max. Bundle Diameter (mm)	15
Min. Loop Tensile Strength (N)	36
Operating Temperature	-76°F (-60°C) - 239°F (115°C)
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
Thickness (mm)	0.8

UV Resistant	No
Width In (mm)	0.07 (1.8)
RoHS Compliancy Status	Compliant
Min. Order Qty.	1,000.0000
