



Search within category

GO

BUY NOW

DESIGN / INSTALL



PRT5EH-C0

Pan-Ty® releasable lashing tie, extra-heavy cross section, 20.1" (511mm) length, weather resistant nylon 6.6, black, bulk package.

Specs

Packaging Details

Documents

★ Add to Favorites

🛒 Add to BOM

Material	Weather Resistant Nylon 6.6
Application	General
Color	Black
Cross Section	Extra-Heavy
Length (In.)	20.1
Length (mm)	511
Locking Style	Releasable
Width (In.)	0.500
Width (mm)	12.7
Min. Loop Tensile Strength Lbs. (N)	250 (1112)
Plenum-Rated	No
UV Resistant	Yes
Tool	Hand install only
Length In (mm)	20.10 (511)
Thickness In (mm)	0.07 (1.9)
Bundle Diameter Range In. (mm)	0.50 (12.7) - 5.00 (127)
CE Compliant	Yes
CSA Certified	No
UL Listed (File #E56854)	No
UL Recognized (File #E56854)	No
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Max. Bundle Diameter (mm)	127
Min. Loop Tensile Strength (N)	1112
Operating Temperature	-76°F (-60°C) - 185°F (85°C)
Part Features	Release tab permits easy rele heavy duty applications.

Request a Quote

Are you looking for a free quote on Panduit Products and Solutions?

Yes, I need a quote!

RoHS Compliancy Status

Compliant

Min. Order Qty.

100.0000

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)

Request a Quote

Are you looking for a free quote on Panduit Products and Solutions?

Yes, I need a quote!