

PLT3S-M0

Pan-Ty® locking tie, standard cross section, 11.5" (292mm) length, weather resistant nylon 6.6, black, bulk package.

Specs | Packaging Details | Tools | Documents

Add to Favorites | Add to BOM

Material	Weather Resistant Nylon 6.6
Application	General
Color	Black
Cross Section	Standard
Locking Style	Locking
Min. Loop Tensile Strength Lbs. (N)	50 (222)
Plenum-Rated	No
Tool	GTS-E, GS2B, GTH-E, GS4H, PTS, PTH, PPTS, STS2, STH2
Length In (mm)	11.5 (292)
Thickness In (mm)	0.052 (1.3)
Bundle Diameter Range In. (mm)	0.06 (1.5) - 3.00 (76)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	—
UL 62275 Compliant (Type 1, 11)	No
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Environment	Outdoor (UV Resistant)
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Min. Loop Tensile Strength (N)	222
Operating Temperature	-76°F (-60°C) - 185°F (85°C)
Part Features	One-piece locking wedge for c ce and high loop tensile strength
Width In (mm)	0.19 (4.8)
RoHS Compliancy Status	Compliant

Request a Quote
Are you looking for a free quote on Panduit Products and Solutions?
Yes, I need a quote!

Min. Order Qty.	1,000.0000

-

Request a Quote
Are you looking for a free quote on Panduit Products and Solutions?

Yes, I need a quote!