



EV18-P47B-L



Disconnect

StrongHold™ Pin Terminal, vinyl insulated, 22 - 18 AWG, .49 pin length.

Find A Distributor

Qty

Add to Borm



- Specifications
- Packaging Detail
- Resources
- Related Products
- Top of Page

Specifications

Base Material	Copper
Insulation Material	Vinyl
Seam Type	Butted Seam
Overall Length (In.)	0.97
Overall Length (mm)	24.6
Color	Red
Maximum Operating Temperature (°C)	105
Maximum Operating Temperature (°F)	221
Pin Length (In.)	0.49
Pin Length (mm)	12.4
Wire Strip Length (In.)	5/16
Wire Strip Length (mm)	7.9
Finish/Coating	Tin-Plated
Maximum Voltage (V)	600
Standards Met	UL
For Use With	CT-100A, CT-260, CT-1550, CT-1551, CT-2300/ST with CD-550, CT-2500/L with CT-2550CH
Barrel Configuration	Funnel Entry
Flammability Rating	V0
Maximum Wire Insulation Diameter (mm)	3.8
Part Number Series	PV
RoHS Compliancy Status	Compliant
Min. Order Qty.	50

Packaging Detail

UPC	07498328162
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0103
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.1031

Resources

Part Drawings	Vinyl Pin Terminal 22-10 awg	US English	View PDF (369 KB)	Download PDF	Share PDF
---------------	------------------------------	------------	-------------------	--------------	-----------

Related Products

P10-P55-D
Pin Terminal, 12 10 AWG, non-insulated, .55 pin length, bulk package.

P10-P55-L
Pin Terminal, 12 10 AWG, non-insulated, .55 pin length, standard package.

P14-P47-C
Pin Terminal, 16 14 AWG, non-insulated, .49 pin length, standard package.